



Skip containers



Asymmetric design [AM]
Symmetric design [SMR]
With steel lids [DMS] or plastic lids [DMR]
With ramp [AMK]

Skip containers

AM, SMR, DMS, DMP, AMK



Skip containers are intended for the transport and storage of municipal and industrial waste. Various special modifications enable the containers to be used for other purposes (manipulation by crane at building sites, mobile storage units, etc.).

Containers are supplied in a variety of styles according to the required use. They are manoeuvred by the boom arms on a skip truck. Containers are painted with a quality corrosion-resistant primer and a top coat in any colour. Selected types can be manufactured in a hot-dip galvanized version.

The containers are manufactured in accordance with DIN 30720.

Standard types

Asymmetric design (AM)

Symmetric design (SMR)

With steel lids (DMS) or plastic lids (DMR)


- spring-assist lid opening,
- lid stops in closed position.
- sealed lids available upon request

• With ramp (AMK)

- sufficiently reinforced for traversing with manual handling equipment,
- 4 massive hinges.

Specifications

- volumes from 5 to 20 m³.
- double-sided triple pivots for tipping,
- forged lifting pins,
- side bar for stacking containers,
- 4-6 mm S235JR bottoms,
- 3-4 mm S235JR side walls,
- stable top profile,
- continuous welds,
- all corners are reinforced,
- perforated tie-down bar for fixing containers on the vehicle per DIN standard,
- hooks for attaching tarpaulin,
- primed on inside surfaces, two coats of primer and two coats of RAL paint on external surfaces.



Kiplager

double-sided triple pivots for tipping



Forged lifting pin

for handling and stacking containers



Asymmetric design (AM)

Type /Code	configuration (mm)			volume (m³)	weight (kg)
	floor	sides	dump side		
AM-5,5-534	5	3	4	5,5	550
AM-5,5-644	6	4	4	5,5	627
AM-7,0-534	5	3	4	7	619
AM-7,0-644	6	4	4	7	713
AM-10,0-534	5	3	4	10	746
AM-10,0-644	6	4	4	10	859



Symmetric design (SMR)

Type /Code	configuration (mm)			volume (m³)	weight (kg)
	floor	sides	dump side		
SMR-5,5-534	5	3	4	5,5	585
SMR-5,5-644	6	4	4	5,5	659
SMR-7,0-534	5	3	4	7	723
SMR-7,0-644	6	4	4	7	819
SMR-10,0-534	5	3	4	10	839
SMR-10,0-644	6	4	4	10	959



Symmetric skips - flat



Symmetric skip - stacking



Securing tarpaulins to a symmetric container

Type with steel lids (DMS)

Type /Code	configuration (mm)			volume (m³)	weight (kg)
	floor	sides	dump side		
DMS-5,5-534	5	3	4	5,5	749
DMS-5,5-644	6	4	4	5,5	824
DMS-7,0-534	5	3	4	7	810
DMS-7,0-644	6	4	4	7	900
DMS-10,0-534	5	3	4	10	960
DMS-10,0-644	6	4	4	10	1075



DMS-7,0

Type with plastic lids (DMR)

Type /Code	configuration (mm)			volume (m³)	weight (kg)
	floor	sides	dump side		
DMP-5,5-534	5	3	4	5,5	730
DMP-5,5-644	6	4	4	5,5	806
DMP-7,0-534	5	3	4	7	790
DMP-7,0-644	6	4	4	7	878
DMP-10,0-534	5	3	4	10	920
DMP-10,0-644	6	4	4	10	1038



DMP-10,0

Type with ramp (AMK)

Type /Code	configuration (mm)			volume (m³)	weight (kg)
	floor	sides	dump side		
AMK-5,5-644	6	4	4	5,5	672
AMK-7,0-644	6	4	4	7	760
AMK-10,0-644	6	4	4	10	916



Ramp

Reinforced tilting dump side used as ramp



AMK-7,0



ELKOPLAST CZ, s.r.o.

Štefánikova 2664
760 01 Zlín
Czech Republic

e-mail: elkoplast@elkoplast.cz
tel.: +420 575 571 000

